


SMD HIGH CURRENT POWER BEAD INDUCTORS



MODEL NO. : SPB-07050 HF SERIES

FEATURES:

- * SUPERIOR QUALITY FOR AN AUTOMATED PRODUCTION LINE.
- * PICK AND PLACE COMPATIBLE.
- * TAPE AND REEL PACKING.
- * FREQUENCY RANGE:UP TO 2 MHZ.
- * COMPLIANT WITH RoHS AND HALOGEN FREE.



APPLICATION :

- * SERVERS.
- * MOTHERBOARD.
- * VGA CARD.

ELECTRICAL SPECIFICATION:

PART NO	INDUCTANCE @0 ADC (nH) ±20%	DCR (mΩ) ±7%	INDUCTANCE @ TEMPERATURE RISE CURRENT (nH) ±20%	TEMPERATURE RISE CURRENT (ADC)	SATURATION CURRENT (ADC) (NOTE 2)
SPB-07050-R07-2 HF	72	0.24	72	31	50
SPB-07050-R10-2 HF	105	0.24	102	31	45
SPB-07050-R12-2 HF	120	0.24	115	31	36
SPB-07050-R15-2 HF	150	0.24	130	31	32


NOTE(1) : Test frequency: 100 KHZ,1Vrms.

NOTE(2) : The saturation current indicates the value of DC current is approximately 20% lower than its initial value of inductance.


NOTE(3) : $\Delta T=40^{\circ}\text{C}$ approximately under the temperature rise current.

NOTE(4): Operating temperature range: $-40^{\circ}\text{C} \sim +150^{\circ}\text{C}$.

PHYSICAL DIMENSION : (UNIT:mm)



INDUCTANCE /TEMPERATURE RISE VS DC BIAS:



PACKAGING SPEC:

1. REEL SIZE & UNITS PER REEL :13",1000PCS.
2. TAPE WIDTH:16mm.
3. REEL WIDTH:22.4mm.
4. COMPONENT PITCH:12mm