


SMD HIGH CURRENT POWER BEAD INDUCTORS



MODEL NO. : SPB-10250 HF SERIES

FEATURES:

- * SUPERIOR QUALITY FOR AN AUTOMATED PRODUCTION LINE.
- * PICK AND PLACE COMPATIBLE.
- * TAPE AND REEL PACKING.
- * FREQUENCY RANGE:UP TO 2 MHZ.
- * COMPLIANT WITH RoHS AND HALOGEN FREE.



APPLICATION :

- * SERVERS.
- * MOTHERBOARD.
- * VGA CARD.

ELECTRICAL SPECIFICATION:

PART NO	INDUCTANCE @0 ADC (nH) $\pm 20\%$	DCR (m Ω) $\pm 7\%$	RATED CURRENT (ADC)	INDUCTANCE @TEMPERATURE RISE CURRENT (nH) $\pm 20\%$	TEMPERATURE RISE CURRENT (ADC)	SATURATION CURRENT (ADC) (NOTE 2)
SPB-10250-R12-2 HF	120	0.31	31	120	31	50
SPB-10250-R15-2 HF	155	0.31	31	150	31	40
SPB-10250-R22-2 HF	220	0.31	31	190	31	33
SPB-10250-R34-2 HF	340	0.31	18	280	31	18

NOTE(1) : Test frequency: 100 KHZ,1Vrms.


NOTE(2) : The saturation current indicates the value of DC current is approximately 20% lower than its initial value of inductance.

NOTE(3) : $\Delta T=40^{\circ}\text{C}$ approximately under the temperature rise current.


NOTE(4) : The rated current represents the DC current that the inductor can tolerate before saturation.

NOTE(5): Operating temperature range: $-40^{\circ}\text{C} \sim +150^{\circ}\text{C}$.

PHYSICAL DIMENSION : (UNIT:mm)



INDUCTANCE /TEMPERATURE RISE VS DC BIAS:



PACKAGING SPEC:

1. REEL SIZE & UNITS PER REEL :13",1000PCS.
2. TAPE WIDTH:24mm.
3. REEL WIDTH:29.5mm.
4. COMPONENT PITCH:12mm