



# 零件承认书



## COMPONENT APPROVAL SHEET

CUSTOMER: \_\_\_\_\_

CUSTOMER P/N: \_\_\_\_\_

B/W P/N: \_\_\_\_\_

DESCRIPTION: **BSMA2313SP Series**

DATE: **2022/5/24**

REV.: **A**

客户签回栏

APPROVED	REVIEWED	PREPARED
邹爱加	管梦东	陈泉明

台北公司：百徽股份有限公司（**BULL WILL CO., LTD.**）  
台北市内湖区瑞湖街 1 9 9 號 3 樓（1 1 4）  
3F.,No.199, Ruihu St., Neihu Dist.,Taipei ,Taiwan, R.O.C. (114)

大陆工厂： 君超电子有限公司  
地址：惠州市博罗县泰美镇板桥工业区  
电话：0752-672-3588      传真：0752-6723568



# 图 面 规 格 变 更 履 历 表

[illegible]

SMD Power Inductor

BSMA2313SP Series

1. Features


- 1. Shielded construction.
- 2. Capable of corresponding high frequency .
- 3. Low loss realized with low DCR.
- 4. High performance (Isat) realized by metal dust core.
- 5. Ultra low buzz noise, due to composite construction.
- 6. 100% Lead(Pb)-Free and RoHS compliant.
- 7. Operating temperature -40~+125℃ (Including self - temperature rise)



2. Applications


- 1. DC/DC converters in distributed power systems.
- 2. DC/DC converter for Field Programmable Gate Array(FPGA).
- 3. Battery powered devices.
- 4. Thin type on-board power supply module for exchanger.
- 5. VRM for server.
- 6. High current, low profile POL converters.
- 7. PDA/notebook/desktop/server and battery powered devices.

3. Dimensions



Series	A(mm)	A'(mm)	B(mm)	C(mm)	D(mm)	E(mm)
BSMA2313	23.5±0.5	22.7±0.3	22.0±0.3	12.6±0.4	5.0±0.4	19.0±0.3

Recommend PC Board Pattern



L(mm)	G(mm)	H(mm)
24.0	12.5	19.6

Note: 1. The above PCB layout reference only.  
2. Recommend solder paste thickness at 0.20mm and above.

4. Part Numbering



A: Series

B: Dimension

C: Type

D: Inductance

E: Inductance Tolerance

BxC.

Standard.

100=10.0uH.

M=±20%.


## 5. Specification

Part Number	Inductance L0 A(uH) ±20%	Heat Rating Current DC I <sub>rms</sub> ( A )		Saturation Current DC I <sub>sat</sub> ( A )		DCR (mΩ) Typ	DCR (mΩ) Max
		Typ	Max	Typ	Max		
BSMA2313SP-1R5M	1.50	62	57	52	48	1.0	1.15
BSMA2313SP-2R2M	2.20	58	52	48	43	1.05	1.25
BSMA2313SP-3R3M	3.30	49	47	41	37	1.5	1.75
BSMA2313SP-4R7M	4.70	47	44	38	34	1.9	2.2
BSMA2313SP-6R8M	6.80	40	36	36	32	2.7	3.1
BSMA2313SP-100M	10.0	33	30	28	20	3.8	4.15
BSMA2313SP-220M	22.0	22	18	15	14	9.2	11
BSMA2313SP-230M	23.0	22	18	15	14	9.2	11
BSMA2313SP-330M	33.0	19	16	12	10.5	13.5	15.4
BSMA2313SP-470M	47.0	17	14	12	10	17.3	20.8
BSMA2313SP-680M	68.0	14	12	12	9.0	26.2	29.5
BSMA2313SP-820M	82.0	12	10	9.0	7.7	31	34.2
BSMA2313SP-101M	100	11	9.5	9.0	7.5	36	40

Note:

1. Test frequency : Ls : 100KHz /1.0V.
2. All test data referenced to 25℃ ambient.
3. Testing Instrument(or equ) : L: HP4284A,CH11025,CH3302,CH1320,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER.
4. Heat Rated Current (I<sub>rms</sub>) will cause the coil temperature rise approximately ΔT of 40℃
5. Saturation Current (I<sub>sat</sub>) will cause L0 to drop approximately 30%.
6. The part temperature (ambient + temp rise) should not exceed 125℃ under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
7. Special inquiries besides the above common used types can be met on your requirement.
8. Rated DC Current : The less value whith is I<sub>rms</sub> or I<sub>sat</sub>

## 6. Material List




NO	Items	Materials
1	Core	Alloy Powder .
2	Wire	Polyester Wire or equivalent.
3	Clip	100% Pb free solder(Ni+Sn---Plating)
4	Ink	Halogen-free ketone

## 7. Reliability and Test Condition

Item	Performance	Test Condition
Operating temperature	-40~+125℃ (Including self - temperature rise)	
Storage temperature	1. -10~+40℃,50~60%RH (Product with taping) 2. -40~+125℃(on board)	
<b>Electrical Performance Test</b>		
Inductance	Refer to standard electrical characteristics list.	HP4284A,CH11025,CH3302,CH1320,CH1320S LCR Meter.
DCR		CH16502,Agilent33420A Micro-Ohm Meter.
Saturation Current (Isat)	Approximately $\Delta L$ 30%.	Saturation DC Current (Isat) will cause L0 to drop $\Delta L$ (%)
Heat Rated Current (Irms)	Approximately $\Delta T$ 40℃	Heat Rated Current (Irms) will cause the coil temperature rise $\Delta T$ (℃). 1.Applied the allowed DC current 2.Temperature measured by digital surface thermometer
<b>Reliability Test</b>		
Life Test	Appearance: No damage. Impedance: within $\pm 15\%$ of initial value Inductance: within $\pm 10\%$ of initial value Q: Shall not exceed the specification value. RDC: within $\pm 15\%$ of initial value and shall not exceed the specification value	Preconditioning: Run through IR reflow for 2 times.( IPC/JEDECJ-STD-020DClassification Reflow Profiles) Temperature: 125 $\pm 2$ ℃ (Inductor) Applied current: rated current Duration: 1000 $\pm 12$ hrs Measured at room temperature after placing for 24 $\pm 2$ hrs.
Load Humidity		Preconditioning: Run through IR reflow for 2 times.( IPC/JEDECJ-STD-020DClassification Reflow Profiles) Humidity: 85 $\pm 2\%$ R.H, Temperature: 85℃ $\pm 2$ ℃ Duration: 1000hrs Min. with 100% rated current Measured at room temperature after placing for 24 $\pm 2$ hrs.
Moisture Resistance		Preconditioning: Run through IR reflow for 2 times.( IPC/JEDECJ-STD-020DClassification Reflow Profiles) 1. Baked at50℃ for 25hrs, measured at room temperature after placing for 4 hrs. 2. Raise temperature to 65 $\pm 2$ ℃ 90-100%RH in 2.5hrs, and keep 3 hours, cool down to 25℃ in 2.5hrs. 3. Raise temperature to 65 $\pm 2$ ℃ 90-100%RH in 2.5hrs, and keep 3 hours, cool down to 25℃ in 2.5hrs,keep at 25℃ for 2 hrs then keep at -10℃ for 3 hrs 4. Keep at 25℃ 80-100%RH for 15min and vibrate at the frequency of 10 to 55 Hz to 10 Hz, measure at room temperature after placing for 1~2 hrs.
Thermal shock		Preconditioning: Run through IR reflow for 2 times.( IPC/JEDECJ-STD-020DClassification Reflow Profiles) Condition for 1 cycle Step1: -40 $\pm 2$ ℃ 30 $\pm 5$ min Step2: 25 $\pm 2$ ℃ $\cong 0.5$ min Step3: 125 $\pm 2$ ℃ 30 $\pm 5$ minNumber of cycles: 500 Measured at room femprature after placing for 24 $\pm 2$ hrs.
Vibration		Preconditioning: Run through IR reflow for 2 times.( IPC/JEDECJ-STD-020DClassification Reflow Profiles) Oscillation Frequency: 10Hz~2KHz~10Hz for 20 minutes Equipment : Vibration checker Total Amplitude: 10g Testing Time : 12 hours(20 minutes, 12 cycles each of 3 orientations) .

## BULL WILL

Item	Performance	Test Condition														
Bending	Appearance: No damage. Impedance: within ± 15% of initial value Inductance: within ± 10% of initial value Q: Shall not exceed the specification value. RDC: within ± 15% of initial value and shall not exceed the specification value	Shall be mounted on a FR4 substrate of the following dimensions: >=0805 inch(2012mm):40x100x1.2mm <0805 inch(2012mm):40x100x0.8mm Bending depth: >=0805 inch(2012mm):1.2mm <0805 inch(2012mm):0.8mm duration of 10 sec.														
Shock		<table><tr><td>Type</td><td>Peak value (g's)</td><td>Normal duration (D) (ms)</td><td>Wave form</td><td>Velocity change (Vi)ft/sec</td></tr><tr><td>SMD</td><td>50</td><td>11</td><td>Half-sine</td><td>11.3</td></tr><tr><td>Lead</td><td>50</td><td>11</td><td>Half-sine</td><td>11.3</td></tr></table>	Type	Peak value (g's)	Normal duration (D) (ms)	Wave form	Velocity change (Vi)ft/sec	SMD	50	11	Half-sine	11.3	Lead	50	11	Half-sine
Type	Peak value (g's)	Normal duration (D) (ms)	Wave form	Velocity change (Vi)ft/sec												
SMD	50	11	Half-sine	11.3												
Lead	50	11	Half-sine	11.3												
Solder ability	More than 95% of the terminal electrode should be covered with solder ◦	Preheat: 150℃,60sec. ◦ Solder: Sn96.5% Ag3% Cu0.5% Temperature: 245±5℃ ◦ Flux for lead free: Rosin. 9.5% ◦ Dip time: 4±1sec. Depth: completely cover the termination														
Resistance to Soldering Heat		Depth: completely cover the termination <table><tr><td>Temperature(℃)</td><td>Time(s)</td><td>Temperature ramp/immersion and emersion rate</td><td>Number of heat cycles</td></tr><tr><td>260 ±5 (solder temp)</td><td>10 ±1</td><td>25mm/s ±6 mm/s</td><td>1</td></tr></table>	Temperature(℃)	Time(s)	Temperature ramp/immersion and emersion rate	Number of heat cycles	260 ±5 (solder temp)	10 ±1	25mm/s ±6 mm/s	1						
Temperature(℃)	Time(s)	Temperature ramp/immersion and emersion rate	Number of heat cycles													
260 ±5 (solder temp)	10 ±1	25mm/s ±6 mm/s	1													
Terminal Strength	Appearance: No damage. Impedance: within ± 15% of initial value Inductance: within ± 10% of initial value Q: Shall not exceed the specification value. RDC: within ± 15% of initial value and shall not exceed the specification value e	Preconditioning: Run through IR reflow for 2 times.( IPC/JEDEC J-STD-020DClassification Reflow Profiles With the component mounted on a PCB with the device to be tested, apply a force(>0805:1kg , <=0805:0.5kg)to the side of a device being tested. This force shall be applied for 60 +1 seconds. Also the force shall be applied gradually as not to apply a shock to the component being tested. 														

Note : When there are questions concerning measurement result : measurement shall be made after  $48 \pm 2$  hours of recovery under the standard condition.

## 8. Soldering and Mounting

### (1) Soldering

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. BULL WILL terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

### (2) Solder re-flow:

Recommended temperature profiles for re-flow soldering in Figure 1.

### (3) Soldering Iron:

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended.

- Preheat circuit and products to 150°C
- Never contact the ceramic with the iron tip
- Use a 20 watt soldering iron with tip diameter of 1.0mm
- 355°C tip temperature (max)
- 1.0mm tip diameter (max)
- Limit soldering time to 4~5sec.




Fig.1





Fig.2

## 9. Friendly reminder

- (1) When there are questions concerning measurement result : measurement shall be made after  $48 \pm 2$  hours of recovery under the standard condition
- (2) This power choke coil itself does not have any protective function in abnormal condition such as overload, short-circuit and open-circuit conditions, etc. Therefore, it shall be confirmed as the end product that there is no risk of smoking, fire, dielectric withstand voltage, insulation resistance, etc. in abnormal conditions to provide protective devices and/or protection circuit in the end product.
- (3) When this power choke coil was used in a similar or new product to the original one, sometimes it might not be able to satisfy the specifications due to different condition of use.
- (4) Dielectric withstanding test with higher voltage than specific value will damage insulating material and shorten its life.
- (5) This power choke coil must not be used in wet condition by water, coffee or any liquid because insulation strength becomes very low in this condition.
- (6) Please consult our company to confirm the reliability of the process required to wash or use or exposure to a chemical solvent used in this product.


## 10. Packaging Information

### (1) Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)
13"x44mm	44.4+2/-0	100±2	13+0.5/-0.2	330

### (2) Tape Dimension




Series	Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	W(mm)	F(mm)	T(mm)	D(mm)
BSMA	2313	25±0.1	23.0±0.1	13.6±0.1	32±0.1	44±0.3	20.2±0.1	0.5±0.05	1.5±0.1

### (3) Packaging Quantity

BSMA	2313
Chip / Reel	80
Inner box	80
Carton	320

### (4) Tearing Off Force



The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions(referenced ANSI/EIA-481-D-2008 of 4.11 stadnard).

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed mm/min
5~35	45~85	860~1060	300

#### Application Notice

- Storage Conditions  
To maintain the solderability of terminal electrodes:
  1. BULL WILL products meet IPC/JEDEC J-STD-020D standard-MSL, level 1.
  2. Temperature and humidity conditions: Less than 40°C and 60% RH.
  3. Recommended products should be used within 12 months form the time of delivery.
  4. The packaging material should be kept where no chlorine or sulfur exists in the air.
- Transportation
  1. Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
  2. The use of tweezers or vacuum pick up is strongly recommended for individual components.
  3. Bulk handling should ensure that abrasion and mechanical shock are minimized.



## 11. Typical Performance Curves

