

SMD HIGH CURRENT INDUCTORS

MODEL NO. : SSC-10050 HF SERIES

FEATURES:

- * SUPERIOR QUALITY FOR AN AUTOMATED PRODUCTION LINE.
- * PICK AND PLACE COMPATIBLE.
- * TAPE AND REEL PACKING.
- * COMPLIANT WITH RoHS AND HALOGEN FREE.

APPLICATION :

- * NOTEBOOK COMPUTERS.
- * MOTHERBOARD.
- * ROUTERS.
- * SERVERS.



ELECTRICAL SPECIFICATION:

PART NO	INDUCTANCE (uH) $\pm 20\%$	DCR $\pm 10\%$ (m Ω)	INDUCTANCE (uH) TYP	TEMPERATURE RISE CURRENT (ADC)	SATURATION CURRENT (ADC) (NOTE 3)
SSC-10050-R15 HF	0.16 $\pm 30\%$	0.51	0.15	28	55
SSC-10050-R35 HF	0.40	0.67	0.35	26	35
SSC-10050-R40 HF	0.50	1.30	0.40	25	25
SSC-10050-R56 HF	0.72	1.30	0.56	24	27
SSC-10050-1R0 HF	1.2	1.90	1.0	20	18
SSC-10050-1R4 HF	1.75	3.50	1.35	15	17
SSC-10050-1R8 HF	2.4	4.75	1.8	13.5	12.5
SSC-10050-2R4 HF	3.2	5.90	2.4	11.5	12.0
SSC-10050-3R3 HF	4.2	7.10	3.3	10	10.5
SSC-10050-4R4 HF	5.5	10.3	4.4	8.5	10.0
SSC-10050-5R0 HF	6.5	12.7	5.0	8.0	9.5
SSC-10050-6R0 HF	7.8	13.8	6.0	7.3	9.0
SSC-10050-7R4 HF	10	16.3	7.4	6.5	8.0
SSC-10050-130 HF	16	33.0	12.7	4.7	6.0


NOTE(1): Test frequency: 100 KHZ, 1Vrms.

NOTE(2): $\Delta T = 40^\circ\text{C}$ approximately under the temperature rise current


NOTE(3): The saturation current indicates the value of DC current is approximately 30% lower than its initial value of inductance.

NOTE(4): Operating temperature range: $-40^\circ\text{C} \sim +150^\circ\text{C}$

INDUCTANCE VS DC BIAS:



PHYSICAL DIMENSION : (UNIT:mm)



PACKAGING SPEC:

1. REEL SIZE & UNITS PER REEL :13",700PCS.
2. TAPE WIDTH:24mm.
3. REEL WIDTH:29.5mm
4. COMPONENT PITCH:16mm